

R-622

1

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
ORIGINAL

FIELD NOTES

OF
THE DEPENDENT RESURVEY

OF

A PORTION OF THE UINTAH INDIAN RESERVATION BOUNDARY

FROM MILEPOST 38 1/2 TO MILEPOST 39,

A PORTION OF THE

WEST BOUNDARY (UINTAH SPECIAL MERIDIAN),

A PORTION OF THE SOUTH BOUNDARY,

AND SUBDIVISIONAL LINES

AND

THE SUBDIVISION OF SECTIONS 29, 30, AND 32,

IN

TOWNSHIP 2 NORTH, RANGE 1 EAST

OF THE UINTAH SPECIAL MERIDIAN
IN THE STATE OF UTAH

EXECUTED BY

Larry V. Judd
Cadastral Surveyor

Under special instructions dated *March 24, 1993*, approved April 27, 1993, which provided for the surveys included under Group Number *801*, and assignment instructions dated *April 19, 1993*.

Survey commenced *June 8, 1993*

Survey completed *July 6, 1993*

INDEX DIAGRAM

Township 2 North, Range 1 East

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
5 19	18 18	12 13			
5 30	17 29	12 28	27	26	25
4 16	14 15	11			
4 31	14 32	11 33	34	35	36
3 9	8 7	6			

Uintah Indian Reservation Boundary.....	Page 2
The Subdivision of Section 29.....	Page 19
The Subdivision of Section 30.....	Page 22
The Subdivision of Section 32.....	Page 25

TOWNSHIP 2 NORTH, RANGE 1 EAST, UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

The following field notes describe the dependent resurvey of a portion of the Uintah Indian Reservation Boundary, from Milepost 38 1/2 to Milepost 39, a portion of the west boundary (Uintah Special Meridian) a portion of the south boundary and subdivisional lines and the subdivision of sections 29, 30, and 32, in T. 2 North, Range 1 East, Uintah Special Meridian, Utah.

HISTORY OF EARLIER SURVEYS

Surveyed by		Retr. or Resurveyed by	
NORTH BOUNDARY			
All	J.H. Martineau	1903	
SOUTH BOUNDARY			
Portion	C.L. Dubois	1875	
Portion	J.H. Martineau	1903	
EAST BOUNDARY			
All	J.H. Martineau	1903	
All		R.A. Zaninovich	1990
WEST BOUNDARY (Uintah Special Meridian)			
All	J.H. Martineau	1903	
Remonumentation		A. Nelson	1961
Remonumentation		F.D. Reynolds	1968
UINTAH INDIAN RESERVATION BOUNDARY			
All	C.L. Dubois	1875	
All		A.H. Brown and F.M. Brown	1903
Remonumentation		A. Nelson	1961
SUBDIVISION			
All	J.H. Martineau	1903	
Portion		V. Lane	1957
Remonumentation		A. Nelson	1961
Remonumentation		F.D. Reynolds	1968
Portion		R.A. Zaninovich	1990

A portion of the Uintah Indian Reservation boundary and a portion of the subdivisional lines were resurveyed by C.F. Miller, R.L.S. 8079, for the U.S.D.A. Forest Service, Ashley National Forest. Corner positions are monumented with standard Forest Service aluminum posts, as described in the body of these notes.

TOWNSHIP 2 NORTH, RANGE 1 EAST, UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group number 801, Utah, dated March 24, 1993.

The directions of lines were determined by references to true meridians established on line by hour angle observations of Polaris. The lines were carried forward by sustained angulations, being supplemented by other observations taken throughout the progress of the survey. Distances were determined by electronic measurement.

Preliminary to the resurvey, the lines of the original survey were retraced and a diligent search was made for any evidence of the original field note record. The retracement data were thoroughly verified and only the true line notes are given herein.

The geographic position of the corner of sections 32, 33, 4 and 5, Tps. 1 and 2 N., R. 1 E. as determined by a tie made to U.S. Geological Survey triangulation station "FAHGARWEE" is as follows:

Latitude 40° 31' 12.14" N. Longitude 109° 53' 47.66" W.
N.A.D. 1927

The mean magnetic declination as projected from the U.S. Geological Survey "Magnetic Declination Map of 1990" is: 13 1/2° East.

Dependent Resurvey of the Uintah Indian Reservation Boundary,
from Milepost 38 1/2 to Milepost 39

Reestablishment of the Survey Executed by C.L. Dubois, Deputy Surveyor
in 1875, and the Resurvey by Brown and Brown, Deputy Surveyors in 1903

Beginning at milepost 38 1/2 on the Uintah Indian Reservation Boundary, monumented with a 2 1/2 in. diam., B.L.M. iron post, firmly set in a mound of stone, with the original monument, a sandstone, 18x12x8 ins., buried on the NE side of the iron post, with brass cap marked as described in the official record of the 1961 remonumentation.

N. 72°26.5' W., between milepost 38 1/2 and milepost 39, on the Uintah Indian Reservation Boundary.

Over open mountainous land

0.555 The closing corner of sections 21 and 28, hereinafter described.

40.160 Milepost 39 on the Uintah Indian Reservation Boundary, monumented with a 2 1/2 in. diam., U.S.D.A. Forest Service aluminum post, firmly set, projecting 8 ins. above ground and a mound of stone to the west, with aluminum cap marked:

DEPENDENT RESURVEY OF THE
 UTAH INDIAN RESERVATION BOUNDARY,
 FROM MILEPOST 38 1/2 TO MILEPOST 39

CHAINS

AP
 39M
 U I R
 1988

This corner is accepted as being at the true corner position, with no improvements made to the monument.

Dependent Resurvey of a Portion of the West Boundary
 (Uintah Special Meridian),
 T. 2 N., R. 1 E., Uintah Special Meridian, Utah

Reestablishment of the Survey Executed by
 J.H. Martineau, Deputy Surveyor in 1903

From the corner of Townships 1 and 2 N., Ranges, 1 E. and 1 W., monumented with a quartzite 24x14x4 ins., firmly set, plainly marked with an X on the top of the rock and 6 grooves on each of the 4 sides, with a scattered mound of stone to the north.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, set in a mound of stone, 4 1/2 ft base to top of aluminum cap marked:

T2N	
R1W	R1E
S36	S31
S1	S6
R1W	R1E
T1N	
1993	

Deposit a clear "Deep-1 magnet" at the base of the aluminum post.

Buried the marked stone alongside.

N. 0°09' W., along the west boundary, between sections 31 and 36.

Over rolling land through burned pinon and juniper.

40.14

The 1/4 section corner of sections 31 and 36, monumented with a quartzite 16x12x10 ins., firmly set, plainly marked SC 1/4 on the west face with a mound of stone to the west.

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY
(UINTAH SPECIAL MERIDIAN),
T. 2 N., R. 1 E., UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, set in a mound of stone, 4 1/2 ft base to top of aluminum cap marked:

T2N
R1W R1E
1/4
S36 | S31
1993

Buried the marked stone alongside.

The corner falls in an old burn area, in scattered live juniper.

N. 0°24' W., beginning new measurement.

19.965 Point for the N 1/16 section corner of sections 31 and 36.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, set in a mound of stone, 5 ft. base to top of aluminum cap marked:

T41S
R1W R1E
N 1/16
S36 | S31
1993

Deposit a clear "Deep-1 magnet" at the base of the aluminum post.

39.73 Fence 4 strand barbwire, bears N. 80° W. and S. 80° E.

39.93 Point for the corner of sections 25, 30, 31, and 36, at proportionate distance. No remaining evidence of the original corner was found.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, set in a mound of stone, 4 1/2 ft. base to top of aluminum cap marked:

T2N
R1W R1E
S25 | S30
S36 | S31
1993

Deposit a clear "Deep-1 magnet" at the base of the aluminum post.

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY
(UINTAH SPECIAL MERIDIAN),
T. 2 N., R. 1 E., UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

N. 0°24' W., along the west boundary, between sections 25 and 30.

Over rolling land through pinon and juniper.

0.41

Center line of paved road, 41 lks. wide, course S. 80° E. and N. 80° W.

39.93

The 1/4 section corner of sections 25 and 30, monumented with a sandstone, 24x16x16 ins., firmly set, plainly marked SC 1/4 on the west face with a scattered mound of stone to the west.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T2N
R1W R1E
1/4
S25 | S30
1993

Raise a mound of stone, 4 ft. base, 3 ft. high, west of the corner.

Buried the marked stone alongside.

The corner falls in old burn area.

N. 0°25' W. beginning new measurement.

40.13

The corner of sections 19, 24, 25, and 30, monumented with a 2 1/2 ins. diam., B.L.M. iron post, firmly set, projecting 5 ins. above ground, with brass cap marked as described in the official record of the 1961 remonumentation.

From which the original 1903 bearing trees, redescribed by the 1961 remonumentation:

A pinon, 14 ins. diam., bears S. 2° E., 50 lks. dist., (record,
S. 1° E., 49 lks. dist.), with faint scribe marks
T2N R1W S30 BT visible on open blaze.

A pinon, 14 ins. diam., bears S. 64° W., 38 lks. dist., (record, S. 66° W.)
with faint scribe marks T2N R1W S25 BT visible on open blaze.

A cedar, 12 ins. diam., bears N. 17°20' W., 11 lks. dist., (record,
N. 21° W.), with faint scribe marks, T2N R1W S24 BT, visible on
open blaze.

No remaining evidence of the NE bearing tree was found.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 2 N., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH

CHAINS

Dependent Resurvey of a Portion of the South Boundary,
T. 2 N., R. 1 E., Uintah Special Meridian, Utah

Reestablishment of the Survey Executed by
J.H. Martineau, Deputy Surveyor in 1903

From the corner of sections 32, 33, 4, and 5, monumented with a sandstone, 18x12x10 ins., firmly set in a scattered mound of stone, plainly marked with 4 grooves on the E and 2 grooves on the W edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, set in a mound of stone, 4 1/2 ft base to top of aluminum cap marked:

T2N	R1E
S32	S33
S5	S4
T1N	
1993	

Deposit a clear "Deep-1 magnet" at the base of the aluminum post.

Buried the marked stone alongside.

The corner falls on a slight westerly slope in scattered cedar.

From this corner U.S. Geological Survey triangulation station "FAHGARWEE" bears S. 43°40.5' E., 95.328 chs. dist., monumented with a standard 3 1/2 in. diam., brass tablet, set in a boulder flush with the ground with reference markers found as described in the official record.

S. 89°44' W., on the south boundary of the township, between sections 32 and 5.

Over rolling ground in scattered juniper and pinon.

0.35 Wash, 24 lks. wide, drains S. 26° E.

14.35 Center line of paved road, 40 lks. wide, course NW and SE.

20.182 Point for the E 1/16 section corner of sections 32 and 5.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 2 N., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH

CHAINS

T2N R1E
E 1/16 $\frac{S32}{S5}$
T1N R1E
1993

Deposit a clear "Deep-1 magnet" at the base of the aluminum post.

Raise a mound of stone, 3 ft. base, 2 ft. high, north of the corner.

The corner falls 11 lks. north of a 4 strand barbwire fence, projecting E and W.

40.364 The 1/4 section corner of sections 32 and 5, monumented with a 20 penny nail, found flush with the ground set in the center of a dirt road 15 lks. wide, course E and W, running within a fenced in lane 1 chain wide. This point has been used as the 1/4 section corner position, and is accepted as a careful and faithful determination of the original corner position.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 8 ins. below ground, with aluminum cap marked:

T2N R1E
1/4 $\frac{S32}{S5}$
T1N R1E
1993

Deposit a clear "Deep-1 magnet" at the base of the aluminum post.

Deposit the nail inside the aluminum post.

From the corner, the corner of fences projecting E, W and N, bears north 50 lks dist., and the corner of fences projecting E, W and S, bears south 50 lks. dist.

S. 89°43' W., beginning new measurement.

20.135 Point for the W 1/16 section corner of sections 32 and 5.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 6 ins. below the ground, with aluminum cap marked:

T2N R1E
W 1/16 $\frac{S32}{S5}$
T1N R1E
1993

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 2 N., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH

CHAINS

The corner falls in the center of a dirt road, 15 lks. wide, course E and W.

From the corner, a culvert 24 ins. diam., running N and S under the road, bears east 5 lks. dist.

40.27

The corner of sections 31, 32, 5, and 6, monumented with a sandstone 20x12x12 ins., firmly set in a mound of stone, plainly marked with 1 groove on the W, and 5 grooves on the E edges.

from which the original bearing trees:

A cedar, 16 ins. diam., bears N. 46° E., 28 lks. dist., with scribe marks
T2N R1E S32 BT visible on partially healed blaze.

A cedar stump 6 ins. diam., bears S. 74° W., 42 lks. dist., with no remaining
scribe marks.

A cedar 6 ins. diam., bears N. 23° W., 28 lks. dist., with scribe
marks T2N R1E S31 BT, visible on open blaze.

At the corner point.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, set in a mound of
stone, 4 1/2 ft base to top of aluminum cap marked:

T2N	R1E
S31	S32
S6	S5
T1N	
1993	

Deposit a clear "Deep-1 magnet" at the base of the aluminum post.

Buried the marked stone alongside.

The corner falls on rocky ground in scattered juniper.

Reestablishment of the Survey Executed by
C.L. Dubois, Deputy Surveyor in 1875

S. 88°31' W., between sections 31 and 6.

Over rolling ground in scattered juniper and pinon.

20.043

The E 1/16 section corner of section 6 only, T. 1 N., R. 1 E., monumented with a sandstone
24x16x12 ins., firmly set, plainly marked 1/16 on the north face.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 2 N., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH

CHAINS

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, set in a mound of stone 4 1/2 ft. base to top of aluminum cap marked:

T2N R1E

E 1/16

S6

T1N R1E

1993

Buried the marked stone alongside.

The corner falls on the bench east of the Whiterocks River, in an old burn area.

S. 89°02' W., beginning new measurement.

16.95 Right bank of the Whiterocks River, bears NW and SE.

20.047 Point for the 1/4 section corner of section 6 only, T. 1 N., R. 1 E., at proportionate distance. No remaining evidence of the original corner was found.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T2N R1E

1/4

S6

T1N R1E

1993

Deposit a clear "Deep-1 magnet" at the base of the aluminum post.

Raise a mound of stone, 5 ft. base, 3 ft. high, north of the corner.

The corner falls in the bottom land area of the Whiterocks River in dense brush and tamarisk.

20.224 Point for the 1/4 section corner of section 31 only, at midpoint between the SE and SW section corners of section 31.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 2 N., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH

CHAINS

T2N R1E
S31
1/4
T1N R1E
1993

Deposit a clear "Deep-1 Magnet" at base of the aluminum post.

23.55

Creek 20 lks. wide, course south.

40.094

The W 1/16 section corner of section 6 only, T. 1 N., R. 1 E., monumented with a sandstone 20x14x12 ins., firmly set, and plainly marked 1/16 on the north face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with aluminum cap marked:

T2N R1E
W 1/16
S6
T1N R1E
1993

Deposit a clear "Deep-1 magnet" at the base of the aluminum post.

Buried the marked stone alongside.

Raise a mound of stone, 3 1/2 ft. base, 2 1/2 ft. high, north of the corner.

S. 88°56' W., beginning new measurement.

20.39

The corner of Townships 1 and 2 North, Ranges 1 East and 1 West, hereinbefore described.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 2 N., R. 1 E., Uintah Special Meridian, Utah

Reestablishment of the Survey Executed by
J. H. Martineau, Deputy Surveyor in 1903

From the corner of sections 32, 33, 4, and 5, on the south boundary of the township, hereinbefore described.

N. 0°13' W., between sections 32 and 33.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 2 N., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH

CHAINS

Over rolling mountainous land.

18.85 Center line of dirt road, 28 lks. wide, course N. 52° W. and S. 52° E.

20.02 Point for the S 1/16 section corner of sections 32 and 33.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T2N R1E
S 1/16
S32 | S33
1993

Raise a mound of stone, 4 ft. base, 3 ft. high, east of the corner.

The corner falls at the head of a drainage, course SW.

40.04 The 1/4 section corner of sections 32 and 33, monumented with a sandstone 14x8x6 ins., firmly set, dimly marked 1/4 on the west face with a scattered mound of stone to the west.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, set in a mound of stone, 5 ft. base to top of aluminum cap marked:

T2N R1E
1/4
S32 | S33
1993

Deposit a clear "Deep-1 magnet" at the base of the aluminum post.

Buried the marked stone alongside.

The corner falls on open rocky ground.

N. 0°24.5' W., beginning new measurement.

40.576 The corner of sections 28, 29, 32, and 33, monumented with a sandstone 16x8x8 ins., firmly set, plainly marked with 2 grooves on the W, and 1 groove on the S sides, and a mound of stone to the west.

At the corner point.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 2 N., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH

CHAINS

T2N	R1E
S29	S28
S32	S33

1993

Deposit a clear "Deep-I magnet" at the base of the aluminum post.

Buried the marked stone alongside.

The corner falls on open rocky ground in old burn area.

N. 0°03.5' W., between sections 28 and 29.

Over rolling mountainous land.

41.16

The 1/4 section corner of sections 28 and 29, monumented with a sandstone, 18x12x8 ins., firmly set, plainly marked 1/4 on the west face, with a small mound of stone to the west.

At the corner point.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, set in a mound of stone, 5 ft. base to top of aluminum cap marked:

T2N	R1E
1/4	
S29	S28

1993

Deposit a clear "Deep-I magnet" at the base of the aluminum post.

Buried the marked stone alongside.

N. 0°17.5' W., beginning new measurement.

40.15

Fence, projecting E and W.

40.36

The corner of sections 20, 21, 28, and 29, monumented with an iron post 2 1/2 ins. diam., firmly set, projecting 6 ins. above the top of a mound of stone with a 4 ft. base, with the brass cap marked as described in the official record of the remonumentation by F.D. Reynolds, in 1968.

Reestablishment of the Survey Executed by
J. H. Martineau, Deputy Surveyor in 1903

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 2 N., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH

CHAINS

S. 86°45' E., between sections 21 and 28.

Ascending over open mountainous land.

38.973

The 1/4 section corner of sections 21 and 28, monumented with a 2 1/2 ins. diam. Forest Service aluminum post, firmly set by C.K. Miller, R.L.S. for the Forest Service in 1988, with aluminum cap marked:

$$\begin{array}{r} \text{T2N R1E} \\ 1/4 \frac{\text{S21}}{\text{S28}} \\ 1988 \end{array}$$

This corner is accepted as a careful and faithful reestablishment of the original 1/4 section corner position by proportionate methods.

The original rock, a sandstone 18x10x8 ins., dimly marked 1/4 was found laying loose nearby. I was unable to determine its original location and used the Forest Service monument for proportionate point.

Raise a mound of stone, 3 1/2 ft. base, 2 ft. high N, of the corner and deposited the original rock within the mound.

S. 86°44' E., beginning new measurement.

28.135

The closing corner of sections 21 and 28, on the Uintah Indian Reservation Boundary, monumented with a Forest Service aluminum post, 2 1/2 ins. diam., firmly set, in a collar of stone, and a mound of stone to the north, as set by C.K. Miller, R.L.S. for the Forest Service in 1988, with aluminum cap marked:

$$\begin{array}{r} \text{UIR} \\ \text{S21} \diagdown \text{C} \\ \text{S28} \diagup \text{C} \\ \text{T2N R1E} \\ 1988 \end{array}$$

Reestablishment of the Survey Executed by
J. H. Martineau, Deputy Surveyor in 1903

From the corner of sections 31, 32, 5, and 6, on the south boundary of the Township, hereinbefore described.

N. 0°01' E., between sections 31 and 32.

Over rolling ground.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 2 N., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH

CHAINS

40.274

Point for the 1/4 section corner of sections 31 and 32 at proportionate distance. No remaining evidence of the original corner was found.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T2N R1E
1/4
S31 | S32
1993

Deposit a clear "Deep-1 magnet" at the base of the aluminum post.

The corner falls on the west edge of a dirt road, at a turn in the road, course N and E.

From this corner, the corner of fences projecting N and E, bears S. 74°47' E., 57.5 lks. dist.

60.411

Point for the N 1/16 section corner of sections 31 and 32.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T2N R1E
N 1/16
S31 | S32
1993

Deposit a clear "Deep-1 magnet" at the base of the aluminum post.

The corner falls 16 lks., dist. E from the center of a dirt road, 15 lks. wide, course N and S, and 52 lks. west of a 4 strand barb wire fence, course N and S.

72.25

Center line of a paved road, 41 lks. wide, course N. 89°30' W. and S. 89°30' E.

80.548

The corner of sections 29, 30, 31, and 32, monumented with a rebar 3/8 in. diam., firmly set, at the corner of fences N and E. This rebar at the fence corner is accepted, as the best available evidence of the original section corner position.

At the corner point.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 2 N., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH

CHAINS

T2N R1E	
<u>S30</u>	<u>S29</u>
S31	S32
1993	

Deposit a clear "Deep-1 magnet" at the base of the aluminum post.

Deposit the rebar inside the aluminum post.

The corner falls 34 lks. dist., E from the center of a dirt road, 15 lks. wide, course N and S.

From the corner of sections 28, 29, 32, and 33.

S. 89°40.5' W., between sections 29 and 32.

Over rolling mountainous land.

40.08

Point for the 1/4 section corner of sections 29 and 32, at proportionate distance. No remaining evidence of the original corner was found.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T2N R1E	
1/4	<u>S29</u>
	S32
1993	

Deposit a clear "Deep-1 magnet" at the base of the aluminum post.

Raise a mound of stone, 4 ft. base, 3 ft. high, north of the corner.

The corner falls on flat rocky ground in an old burn area.

57.70

Center line of improved dirt road, 44 lks. wide, course N. 15° W. and S. 34° E.

60.12

Point for the W 1/16 section corner of sections 29 and 32.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T2N R1E	
W 1/16	<u>S29</u>
	S32
1993	

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 2 N., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH

CHAINS

Deposit a clear "Deep-1 magnet" at the base of the aluminum post.

Raise a mound of stone, 4 ft. base, 3 ft. high, north of the corner.

The corner falls on flat ground in scattered juniper.

60.85 Whiterocks Canal, 22 lks. wide, bears N. 44° W. and S. 44° E.

75.15 Point for the W-W-W 1/256 section corner of sections 29 and 32.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

	T2N R1E
W-W-W 1/256	<u>S29</u>
	S32
	1993

Raise a mound of stone, 4 ft. base, 3 ft. high, north of the corner.

The corner falls on flat open ground.

80.16 The corner of sections 29, 30, 31, and 32.

S. 88°32.5' W., between sections 30 and 31.

Over flat open ground.

20.23 Point for the E 1/16 section corner of sections 30 and 31.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 15 ins. in the ground, set in a mound of stone, 5 ft. base to top of aluminum cap marked:

	T2N R1E
E 1/16	<u>S30</u>
	S31
	1993

Deposit a clear "Deep-1 magnet" at the base of the aluminum post.

40.46 Point for the 1/4 section corner of sections 30 and 31, at proportionate distance. The original corner a sandstone, 19x19x8 ins., was found lying loose in a disturbed area. I was unable to determine its original position and therefore it was not used as the corner position.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 15 ins. in the ground, set in a mound of stone, 5 ft. base to top of aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 2 N., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH

CHAINS

T2N R1E
1/4 S30
 S31
 1993

Deposit a clear "Deep-1 magnet" at the base of the aluminum post.

Placed the marked rock within the mound.

78.85 Center line of a paved road 41 lks. wide, course S. 80° E. and N. 80° W.

80.92 The corner of sections 25, 30, 31, and 36 on the west boundary of the township, hereinbefore described.

From the corner of sections 29, 30, 31, and 32.

N. 0°03.5' W., between sections 29 and 30.

Over flat ground, in cultivated field area.

20.175 Point for the S 1/16 section corner of sections 29 and 30.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T2N R1E
S 1/16
S30 | S29
1993

Deposit a clear "Deep-1 magnet" at the base of the aluminum post.

The corner falls 1 lk. N of an E and W fence line and 21 lks. E of the center line of a dirt road, 15 lks. wide, course N and S, and 32 lks. E of the corner of fences bearing E, W, and S, at a gate post.

39.35 Center of Whiterocks canal, 17 lks. wide, bears N. 45° W. and S. 45° E.

40.35 The 1/4 section corner of sections 29 and 30, monumented with a sandstone 16x12x6 ins., plainly marked 1/4, found laying loose on top of the ground alongside a rebar 5/8 in. diam., firmly set.

At the rebar.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 2 N., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH

CHAINS

T2N R1E
1/4
S30 | S29
1993

Deposit a clear "Deep-1 magnet" at the base of the aluminum post.

Raise a mound of stone, 4 ft. base, 3 ft. high, west of the corner.

The corner falls 87 lks. dist., E from the east edge of the Whiterocks canal, 17 lks. wide, bears N. 45° W. and S. 45° E.

N. 0°05.5' W., beginning new measurement.

40.335

The corner of sections 19, 20, 29, and 30, monumented with a B.L.M. iron post, 2 1/2 ins. diam., firmly set in a mound of stone, with brass cap marked as described in the official record of the 1961 remonumentation.

from which the original 1903 bearing trees:

A cedar stump was found at N. 55° E., 193 lks. dist., with
no remaining scribe marks (bearing is 1961 official record).

There is no remaining evidence of the SE or NW bearing trees.

From this corner, S. 75°45' E., 13.56 ft. dist., I found a 3 1/2 ins. diam. brass cap reference monument with an arrow pointing at the section corner, set flush on top of a concrete piling supporting a cattle guard, with brass cap marked as described in the official record of the 1961 remonumentation.

From the corner of sections 20, 21, 28, and 29.

S. 87°39.5' W., between sections 20 and 29.

Over rolling mountainous lands.

41.26

The 1/4 section corner of sections 20 and 29, monumented with an iron post 2 1/2 ins. diam., firmly set in a mound of stone, with brass cap marked as described in the official record of the remonumentation by F.D. Reynolds, in 1968.

The corner falls in a 4 strand barbwire fence, projecting E and W, on a gradual SE slope.

N. 89°25' W., beginning new measurement.

38.40

Center line of improved dirt road, 40 lks. wide, course N and S.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 2 N., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH

CHAINS

38.785

The corner of sections 19, 20, 29, and 30.

S. 86°42' W., between sections 19 and 30.

Over rolling land, through old burn area.

41.59

The 1/4 section corner of sections 19 and 30, monumented with an iron post 2 1/2 ins. diam., firmly set in a collar of stone with brass cap marked as described in the official record of the remonumentation executed by F.D. Reynolds, in 1968.

S. 89°35' W., beginning new measurement.

39.815

The corner of sections 19, 24, 25 and 30 on the west boundary of the township, hereinbefore described.

The Subdivision of Section 29,
T. 2 N., R. 1 E., Uintah Special Meridian, Utah

From the 1/4 section corner of sections 29 and 32.

N. 1°00' W., on the N - S center line of section 29.

20.375

Point for the center S 1/16 section corner of section 29.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, set in a mound of stone, 5 ft. base to top of aluminum cap marked:

T2N R1E
C
S 1/16 | S29
C
1993

Deposit a clear "Deep-1 magnet" at the base of the aluminum post.

40.75

Point for the center 1/4 section corner, at intersection with the E - W center line of section 29.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, set in a mound of stone, 4 ft. base to top of aluminum cap marked:

THE SUBDIVISION OF SECTION 29,
T. 2 N., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH

CHAINS

T2N R1E
C 1/4
S29
1993

Deposit a clear "Deep-1 magnet" at the base of the aluminum post.

80.07 The 1/4 section corner of sections 20 and 29.

From the 1/4 section corner of sections 28 and 29.

S. 89°06' W., on the E - W center line of section 29.

40.752 The center 1/4 section corner.

60.456 Point for the center W 1/16 section corner of section 29.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, set in a mound of stone, 4 ft. base to top of aluminum cap marked:

T2N R1E
C W 1/16 C
S29
1993

Deposit a clear "Deep-1 magnet" at the base of the aluminum post.

70.20 Center line of improved dirt road, 44 lks. wide, course N. 28° W. and S. 28° E.

75.234 Point for the C-W-W-W 1/256 section corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T2N R1E
C-W-W-W 1/256
S29
1993

Deposit a clear "Deep-1 magnet" at the base of the aluminum post.

80.160 The 1/4 section corner of sections 29 and 30.

THE SUBDIVISION OF SECTION 29,
T. 2 N., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH

CHAINS

From the W 1/16 section corner of sections 29 and 32.

N. 0°32' W., on the N - S center line of the SW 1/4 of section 29.

20.275

Point for the SW 1/16 section corner, at intersection with the E - W center line of the SW 1/4 of section 29.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T2N R1E
SW 1/16
S29
1993

Raise a mound of stone, 4 ft. base, 2 ft. high, west of the corner.

The corner falls on a gradual westerly slope in old burn area.

40.55

The center W 1/16 section corner.

From the center S 1/16 section corner of section 29.

S. 89°23' W., on the E - W center line of the SW 1/4 of section 29.

19.872

The SW 1/16 section corner of section 29.

24.10

Center line of improved dirt road 44 lks. wide, course NW and SE.

34.776

Point for the C-W-W-SW 1/256 section corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 30 ins. in the ground, with aluminum cap marked:

T2N R1E
C-W-W-SW
S29
1993

Deposit a clear "Deep-1 magnet" at the base of the aluminum post.

The corner falls on the N edge of a dirt access road, 12 lks. wide, course E and W, at the N end of a hay field, 5 lks. S of a E and W net wire fence.

39.744

The S 1/16 section corner of sections 29 and 30.

THE SUBDIVISION OF SECTION 29,
T. 2 N., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH

CHAINS

From the W-W-W 1/256 section corner of sections 29 and 32.

N. 0°10.5' W., on the N - S center line of the W 1/2 of the SW 1/4, of the SW 1/4 of section 29.

20.20

The C-W-W-SW 1/256 section corner of section 29.

N. 0°10.5' W., on the N - S center line of the W 1/2 of the NW 1/4 of the SW 1/4 of section 29.

20.20

The C-W-W-W 1/256 section corner of section 29.

The Subdivision of Section 30,
T. 2 N., R. 1 E., Uintah Special Meridian, Utah

From the 1/4 section corner of sections 30 and 31.

N. 0°51.5' W., on the N - S center line of section 30.

20.065

Point for the center S 1/16 section corner of section 30.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 30 ins. in the ground, with aluminum cap marked:

T2N R1E
C
S 1/16 | S30
C
1993

Raise a mound of stone, 4 ft. base, 2 ft. high, east of the corner, and set a 6 ft. steel fence post alongside the aluminum post.

The corner falls on the E edge of a dirt road 15 lks. wide, course N and S.

40.13

Point for the center 1/4 section corner, at intersection with the E - W center line of section 30.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, set in a mound of stone, 4 ft. base to top of aluminum cap marked:

T2N R1E
C 1/4
S30
1993

THE SUBDIVISION OF SECTION 30,
T. 2 N., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH

CHAINS

Deposit a clear "Deep-1 magnet" at the base of the aluminum post.

From the corner a dirt road, 17 lks. wide, course NW and SE, bears W 46 lks. dist.

The corner falls on flat ground in old burn area.

79.33

The 1/4 section corner of sections 19 and 30.

From the 1/4 section corner of sections 29 and 30.

S. 88°15' W., on the E - W center line of section 30.

10.255

Point for the C-E-E 1/64 section corner of section 30.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T2N R1E
C-E-E
1/64
S30
1993

Deposit a clear "Deep-1 magnet" at the base of the aluminum post.

Raise a mound of stone, 4 ft. base, 2 1/2 ft. high, north of the corner.

The corner falls in an old cat trail, in scattered live and burned cedar.

20.51

Point for the center E 1/16 section corner of section 30, falls within a swampy area next to the Whiterocks River. Not monumented:

24.00

Left bank of the Whiterocks River 70 lks. wide, bears NW and SE.

41.02

The center 1/4 section corner.

81.155

The 1/4 section corner of sections 25 and 30 on the west boundary of the township, hereinbefore described.

From the E 1/16 section corner of sections 30 and 31.

N. 0°27.5' W., on the N - S center line of the SE 1/4 of section 30.

20.12

Point for the SE 1/16 section corner at intersection with the E - W center line of the SE 1/4 of section 30.

THE SUBDIVISION OF SECTION 30,
T. 2 N., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T2N R1E
SE 1/16
S30
1993

Deposit a clear "Deep-1 magnet at the base of the aluminum post.

Raise a mound of stone, 5 ft. base, 3 ft. high, west of the corner.

The corner falls on the bench E of the Whiterocks River, on flat rocky ground.

40.24 Point for the center E 1/16 section corner of section 30.

From the S 1/16 section corner of sections 29 and 30.

S. 88°24' W., on the E - W center line of the SE 1/4 of section 30.

10.185 Point for the C-E-SE 1/64 section corner of section 30.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, set in a mound of stone, 4 1/2 ft. base to top of aluminum cap marked:

T2N R1E
C-E-SE
S30
1993

Deposit a clear "Deep-1 magnet at the base of the aluminum post.

The corner falls 5 lks. N and 3 lks. E from the corner of fences projecting N and E.

20.37 The SE 1/16 section corner.

28.00 Whiterocks River (scaled).

40.74 The center S 1/16 section corner.

From the C-E-SE 1/64 section corner of section 30.

N. 0°15.5' W., on the N - S center line of the NE 1/4, of the SE 1/4, of section 30.

20.148 The C-E-E 1/64 section corner.

THE SUBDIVISION OF SECTION 32,
T. 2 N., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH

CHAINS

The Subdivision of Section 32,
T. 2 N., R. 1 E., Uintah Special Meridian, Utah

From the 1/4 section corner of sections 32 and 5, on the south boundary of the township,
hereinbefore described.

N. 0°07' W., on the N - S center line of section 32.

19.74 Fence projecting E and W.

20.075 Point for the center S 1/16 section corner of section 32.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, set in a mound of
stone, 4 ft. base to top of aluminum cap marked:

T2N R1E
C
S 1/16 | S32
C
1993

Deposit a clear "Deep-1 magnet" at the base of the aluminum post.

From the corner, a fence projecting N and S, bears E, 24 lks. dist.

40.02 A dirt irrigation ditch, 10 lks. wide, course N. 66° E. and S. 66° W.

40.15 Point for the center 1/4 section corner, at intersection with the E - W center line of section 32.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with aluminum cap
marked:

T2N R1E
C 1/4
S32
1993

Deposit a clear "Deep-1 magnet" at the base of the aluminum post.

60.362 Point for the center N 1/16 section corner of section 32.

THE SUBDIVISION OF SECTION 32,
T. 2 N., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with aluminum cap marked:

T2N R1E
C
N 1/16 | S32
C
1993

Deposit a clear "Deep-1 magnet" at the base of the aluminum post.

The corner falls on flat open ground.

65.90

Center line of paved road, 41 lks wide, course NW. and SE.

80.574

The 1/4 section corner of sections 29 and 32.

From the 1/4 section corner of sections 32 and 33.

S. 89°53.5' W., on the E - W center line of section 32.

20.146

Point for the center E 1/16 section corner of section 32.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, set in a mound of stone 6 ft. base to top of aluminum cap marked:

T2N R1E
C — E 1/16 — C
S32
1993

Deposit a clear "Deep-1 magnet" at the base of the aluminum post.

The corner falls on a gradual westerly slope.

27.90

Center line of paved road, 41 lks. wide, course NW and SE.

30.219

Point for the C-W-E 1/64 section corner of section 32.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, set in a mound of stone, 5 ft. base to top of aluminum cap marked:

THE SUBDIVISION OF SECTION 32,
T. 2 N., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH

CHAINS

T2N R1E
C-W-E 1/64
S32
1993

30.40 Center of dirt road, 15 lks. wide, course N and S.

30.60 East edge of Whiterocks canal, 12 lks. wide, bears NW and SE.

40.292 The center 1/4 section corner.

60.38 Point for the center W 1/16 section corner of section 32.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 6 ins. below ground with aluminum cap marked:

T2N R1E
C — W 1/16 — C
S32
1993

The corner falls in a access gate into a pasture.

The corner falls 12 lks. W, of the corner of fences projecting S and W.

80.468 The 1/4 section corner of sections 31 and 32.

From the E 1/16 section corner of sections 32 and 5, on the south boundary of the township, hereinbefore described.

N. 0°10' W., on the N - S center line of the SE 1/4 of section 32.

20.047 Point for the SE 1/16 section corner at intersection with the E - W center line of the SE 1/4 of section 32.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T2N R1E
SE 1/16
S32
1993

THE SUBDIVISION OF SECTION 32,
T. 2 N., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH

CHAINS

Deposit a clear "Deep-1 magnet" at the base of the aluminum post.

Raise a mound of stone 4 ft. base, 2 ft. high, west of the corner.

23.60

Center line of a paved road, 41 lks. wide, course N. 18° W. and S. 18° E.

40.094

The center E 1/16 section corner of section 32.

From the S 1/16 section corner of sections 32 and 33.

S. 89°49' W., on the E - W center line of the SE 1/4 of section 32.

19.01

Center line of a paved road, 41 lks. wide, course N. 18° W. and S. 18° E.

20.164

The SE 1/16 section corner.

30.246

Point for the C-W-SE 1/64 section corner of section 32.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 30 ins. flush with the ground with aluminum cap marked:

T2N R1E
C-W-SE
1/64
S32
1993

Deposit a clear "Deep-1 magnet" at the base of the aluminum post.

Set a cedar post 5 ins. diam., 7 ft. long, alongside the aluminum post.

The corner falls in open pasture.

40.328

The center S 1/16 section corner.

From the C-W-SE 1/64 section corner of section 32.

N. 0°08.5' W., on the N - S center line of the NW 1/4 of the SE 1/4 of section 32.

20.06

The C-W-E 1/64 section corner.

THE SUBDIVISION OF SECTION 32,
T. 2 N., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH

CHAINS

From the W 1/16 section corner of sections 32 and 5, on the south boundary of the township, hereinbefore described.

N. 0°03' W., on the N - S center line of the SW 1/4 of section 32.

40.212 The center W 1/16 section corner.

N. 0°03' W., on the N - S center line of the NW 1/4 of section 32.

20.175 Point for the NW 1/16 section corner at intersection with the E - W center line of the NW 1/4 of section 32.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with aluminum cap marked:

T2N R1E
NW 1/16
S32
1993

Deposit a clear "Deep-1 magnet" at the base of the aluminum post.

Raise a mound of stone, 3 ft. base, 3 ft. high, west of the corner.

40.35 The W 1/16 section corner of sections 29 and 32.

From the center N 1/16 section corner of section 32.

S. 89°47' W., on the E - W center line of the NW 1/4 of section 32.

19.45 Creek 6 lks. wide, bears N and S.

20.065 The NW 1/16 section corner.

40.13 The N 1/16 section corner of sections 31 and 32.

General Description

This area surveyed in T. 2 N., R. 1 E. Uintah Special Meridian, is located approximately 7 miles northeasterly of the town of Whiterocks, Utah. The elevation varies from approximately 6500 to 7500 ft. The terrain varies from cultivated fields and pasture, bottom lands along the Whiterocks River and mountainous lands, vegetated with scattered live pinon and juniper in old burn area.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Name	Capacity
Shawn L. Peterson	Survey Technician
Jennifer Eames	Survey Technician
Shane Button	Survey Aid
Cecil Cornpeach	Volunteer


CERTIFICATE OF SURVEY

I, **Larry V. Judd, Cadastral Surveyor**, hereby certify upon honor that, in pursuance of special instructions bearing the date of the **24th day of March, 1993**, I have *dependently resurveyed a portion of the Uintah Indian Reservation boundary, from Milepost 38 1/2 to Milepost 39, a portion of the west boundary (Uintah Special Meridian), a portion of the south boundary, and subdivisional lines; and subdivided sections 29, 30, and 32, in Township 2 North, Range 1 East,*

of the **Uintah Special Meridian**, in the State of **Utah**, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

September 30, 1997

Date



(Cadastral Surveyor)

Date

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Salt Lake City, Utah

The foregoing field notes of the *dependent resurvey of a portion of the Uintah Indian Reservation Boundary, from Milepost 38 1/2 to Milepost 39 a portion of the West Boundary (Uintah Special Meridian), a portion of the south boundary, and subdivisional lines; and subdivided sections 29, 30, and 32, in Township 2 North, Range 1 East, Uintah Special Meridian, Utah.*

executed by **Larry V. Judd, Cadastral Surveyor**

having been critically examined and found correct, are hereby approved.

March 18, 1998

Date



(Chief Cadastral Surveyor for Utah)